

Produces a perfect bed for paving stones

Optimas® Maxi-Screed



Optimas®

Levelling of the bedding properly is half paved.

So they love to rest ... the paving stones

Optimas Maxi-Screed is the ideal tool to prepare the laying course for paving. Innovative modular design caters for any width as opposed to telescopic design which has proved to be ineffective.

The well-thought construction allows tidy leveling of subbase (sand, gravel, etc.) as well as the precise leveling of the bedding up to width of 7 m.

Due to the extremely simple operation, the high efficiency and the comparatively small investment sum it is a tool that belongs on each paving job-site.

Optimas Maxi-Screed consists of:

- 1 set of wheels with flaps, handles and chains
- Intermediate pieces and adapter
- Transport hooks
- 60 m screed-rails (12x4m, 4x2m, 4x1m)

The advantages of the Optimas Maxi-Screed:

- Working width is variable from 250 mm to 7500 mm through fast and easy connection of intermediate pieces in a modular system.
- Separate height-adjustable wheels on each side. Can be pulled on existing kerbs (raised or flat), gutters or Optimas rails
- Movable side flaps provide clean and precise screeding along the edges.
- Maxi-Screed-board can either ride on existing kerbs, gutters or Optimas rails
- High capacity for filling material through bucket shape.
- Easy replacement and connection of intermediate pieces.
- Hardened and ground spring steel blade
- Space-saving transport through modular system
- A crown of up to 9 % can be adjusted
- Versatility through the use on small and large construction sites for coarse gravel mixture and fine bedding (e.g. sidewalks, residential streets, parking lots, industrial yards, port projects)



Simple transportation of a mounted Maxi-Screed system



Height adjustable wheels ride on kerbs and screed rails



Movable side flaps provide clean and precise screeding along the edges



Screeding of coarse gravel mixture with central elevation (Crown)

Talk to us!

Optimas[®]
Paving Specialist

Optimas Maschinenfabrik
H. Kleinemas GmbH
Industriestraße 12
D-26683 Saterland-Ramsloh
Tel.: +49-(0)4498/92 42 -0
Fax: +49-(0)4498/92 42 -42
e-mail: info@optimas.de
www.PavingSpecialist.com



Screeding of 5.5 meter accurately between kerb and gutter.