



Putzmeister

Your benefits

- Robust design – tested in construction site use and on the test track
 - Supports a variety of worm pumps through to the 2L8
 - Reliable remote control makes possible a variety of functions
 - Central control with intuitive keypad and clearly arranged display
 - Larger tank for maximum operational performance without refuelling
 - Support feet for optimal stability on the construction site
-
- Robust plastic cover according to the highest quality standard for maximum durability
 - Safe transfer of machine with crane – thanks to integrated crane lugs



STAGE V
ready to work

SP 25 DHF – robust and powerful, for large volumes of self-levelling floor screed

The powerful SP 25 DHF auger pump is suitable for conveniently and reliably placing large volumes of self-levelling floor screed. Thanks to the strong three-cylinder diesel engine with 37 kW and “Stage V” emissions, the pump can be operated without issues in the whole of the EU and Switzerland now and in future. The increased efficiency focuses on higher throughputs, longer delivery ranges and higher delivery pressures.

The large filling area features a swinging spray guard and a powerful vibrating screen. The low filling height facilitates loading on the construction site as well as the final cleaning. The low pump weight also makes for easier handling on the construction site.

Your expert Putzmeister dealer will be glad to provide you with further information according to your individual requirements.

Self levelling
floor screed

- **Calcium sulphate screed (anhydrite)**
- **Cement floor screed**



Shotcrete

- **Shotcrete with a grain size up to 8 mm**





The central control panel with intuitive keypad increases operating safety. A clearly structured display behind scratch-resistant protective glass supplies the machine operator with all relevant information.



Conveyor with a volume of 250 l, a larger filling area and a swinging spray guard – with a powerful vibrator as standard. Lower filling height facilitates final cleaning and loading by truck mixer.



The powerful, turbocharged diesel engine with 37 kW and diesel particle filter complies with the requirements of the exhaust emissions standard "Stage V". This means that the pump can be operated in the EU and Switzerland without issues.

Technical data

SP 25 DHF

Feed hopper	250 l
Pump	Worm pump 7515 Premium
Delivery rate*	up to 20 m ³ /h
Delivery pressure	35 bar
Delivery range**	150 – 200 m
Tank capacity	40 l
Engine	3-cylinder Kubota Diesel, 37 kW at 2 700 rpm (Stage V)
Weight	1 050 kg
Length × width × height	4 280 × 1 410 × 1 300 mm
Filling height	730 mm
Maximum particle size	8 mm
Chassis	braked, approved for road use

Equipment

Car coupling	■
Lifting eye	■
Radio remote control with output regulation + Engine On/Off	■
Support legs	■
Supporting wheel	■
Tool box	■
Vibrating screen with 15 mm mesh width (grid)	■
Vibrator	■
High-pressure cleaner	□
Special painting canopy in RAL colour	□
Truck coupling	□
Working lights	□
Worm parts 2L8 (max. grain size 12 mm)	□

* The delivery rate is theoretical and depends on the pump pressure.

** The data is based on experience and is dependent on the materials used.

□ Optional ■ Standard

Putzmeister Mörtelmaschinen GmbH

Max-Eyth-Straße 10 · 72631 Aichtal / Germany
 P.O.Box 2152 · 72629 Aichtal / Germany
 Tel. +49 7127 599-0 · Fax +49 7127 599-743
 mm@putzmeister.com · www.putzmeister.com

