FUH20

Portable Frequency Converters





With just 8.9 kg, the frequency converter FUH20 is a real lightweight, is easy to transport on the job site and therefore flexible in application. The high frequency technology not only saves weight, but also provides a reliable and sturdy performance. The high frequency technology has already been time-tested and absolutely proven to be reliable in other industries and is now used by Wacker Neuson for frequency converters.

- Frequency converter with a plug receptacle, 20 amps
- New high-frequency technology top performance with compact dimensions and low weight
- Flexibly movable due to the practical carrying handle
- Efficient cooling fins design. Absolutely reliable, even in the event of dirt accumulation from concrete.
- Long service life, thanks to the extremely durable aluminum housing

FUH20 Technical specifications

LxWxH	545 x 138 x 241 mm
Weight	8.9 kg
Frequency converter	no
Input voltage	230 V
Output voltage	42 V
Input frequency	50 Hz
Output frequency	200 Hz
Input current 1~	7.8 A
Output current 3~	20 A
Input performance	1.8 kVA
Output performance	1.4 kVA
Power factor	0.8 cos Φ 1~
Protection class	IP44
Power cable	1.5 m
Plug type	CEE 7/7 (model EF)
Receptacles Quantity	1
Receptacles Model	CEE 3P 32 A 4 H 50 V 100-200 Hz

Please note: that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2021 Wacker Neuson SE.