Electronic frequency convertersPortable Frequency Converters







Lightweight, robust and high capacity

The outstanding feature of the FUE range of frequency converters is its lightweight, compact design. Thanks to their aluminium construction they are very easy to handle. Their high-quality electronics and active cooling system ensure maximum performance even in continuous operation. The intelligent voltage and power management is particularly practical. It compensates for fluctuations of mains input voltage, wrongly dimensioned extensions or appliances with greatly varying use of power.

- Maintenance-free
- Intelligent voltage and power management

Electronic frequency converters Technical specifications

	FUE-M/T13A	FUE-M/S75A	FUE-M/S85A
LxWxH mm	520 x 310 x 450	520 x 310 x 494	500 x 500 x 550
Weight kg	29	29.5	42
Input voltage 3~ V	400	400	400
Output voltage 3~ V	250	42	42
Input frequency Hz	50 - 60	50 - 60	50 - 60
Output frequency Hz	0 - 200	0 - 200	0 - 200
Input current A	13	13	13.7
Output current A	13	75	85
Input performance kVA	9	9	9
Output performance kVA	5.5	5.5	6.2
Protection class	IP 44	IP 44	IP 44
Power cable m	2.5	2.5	2.5
Receptacles	4	2/4/6	2 / 4

Please note: that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2021 Wacker Neuson SE.