

# DF16

## Rebar Tier



**WACKER  
NEUSON**  
*all it takes!*



### Tying reinforcing steel intelligently: DF 16

The rebar tier DF 16 offers labor relief well worth having. The mechanical device uses a proven twin wire mechanism which ties up to 1,000 uniform and firmly tied knots per hour. The times when reinforcing steel was tied bending down with pliers are over, because the DF 16 is easily operated with just one hand and in an upright position. A professional tool for traditional rebar jobs as well as for fastening plastic ducts for the activation of construction components.

- Up to 1,000 knots per hour
- Mechanical device concept: Independent of battery life and recharging times
- No scrap wire to dispose of
- The magazine of 77 single ties is changed easily
- Also suitable for the activation of construction components

## DF16 Technical specifications

L x W x H with handle retracted	656 x 164 x 118 mm
L x W x H with handle extended	883 x 164 x 118 mm
Weight	2.2 kg
Quantity Ties per tie strip	77
Tie wire material	Copper-plated wire
Diameter of the tie wire	1.1 mm
Tying speed approx.	1000 knots/h
Time required per knot	0.8 sec
Diameter of the round materials to be fastened (min.)	6 + 6 mm
Diameter of the round materials to be fastened (max.)	16 + 16 mm
Order quantities of the ties	Box = 7700 pieces, pallet = 138600 pieces

Please note: that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2021 Wacker Neuson SE.